

Glass rooflight

The flat roof window for stylish settings



- High-quality product
- Second drainage level
- Good thermal insulation
- Straight-line design
- For new buildings and renovations
- Flexible sizes



Daylight and fresh air — also for flat roofs.
With the glass rooflight, INDU LIGHT offers solutions for flat roofs which are also suitable for residential living areas due to their superlative thermal insulation.



Horizontal installation of a large double glazed pane, e.g. for executive-standard private residential construction

The glass rooflight comprises a wing element and a kerb. This is a rigid construction and it can be supplied as a ventilated unit.

Superlative thermal insulation characteristics

The wing element is made from thermally separated extruded aluminium and provides superlative thermal insulation characteristics. This contemporary form of double glazing comprises floatglass and composite safety glass (CSG), incorporated in a cover frame and with gasket seals embedded in the profile sections. As an option, tinted glass panels and single-glazed safety glass (ESG) can also be used as an optional form of solar protection.

On request, we can provide triple glazing as an ultra-thermally insulated variant and with a U_{total} of 0.7 W/m²K. The aluminium profile sections are painted in pure-white RAL 9010, but other RAL colours may also be selected. In the ventilated version, chain drives can be used, optionally in concealed versions, and also as versions integrated in the kerb. It is based on a kerb made of GFP or a steel kerb with the option of pre-installed thermal insulation.

Technical details

Nominal sizes*	50x150	60x90	70x140	80x80	90x90	100x100	120x120	100x150	150x150	180x150 (2 glass panes)	100x200 (2 glass panes)
Double glazing	Float/CSG, optional: ESG/CSG or tinted glass										
INDU LIGHT Glass rooflight	Double glazing U_{total} : 1.1 W/m ² K / triple glazing U_{total} : 0.7 W/m ² K / sound reduction index: 37 dB										
Paint coating	Pure white RAL 9010, optional: other RAL colours										
Rigid glazing version	Optional: ventilated, concealed chain drive / ventilated, integrated chain drive										

* individual dimensions and shapes available on request

INDU LIGHT
 Produktion & Vertrieb GmbH
 Willi-Brundert-Strasse 3
 D-06132 Halle/Saale
 Tel.: +49 (0)345 7 72 96 - 0
 Fax: +49 (0)345 7 72 96 - 11
 E-mail halle@indu-light.de
 www.indu-light.de

INDU LIGHT
 Produktion & Vertrieb GmbH
 Lauterbachstrasse 38
 D-78586 Deilingen
 Tel.: +49 (0)7426 52 70 - 0
 Fax: +49 (0)7426 38 11
 E-mail deilingen@indu-light.de

INDU LIGHT
 West Vertrieb GmbH
 Schützenwall 30
 D-48653 Coesfeld
 Tel.: +49 (0)2541 92 62 - 0
 Fax: +49 (0)2541 92 62 - 12
 E-mail coesfeld@indu-light.de

INDU LIGHT
 Indu-Light AG / SA
 Industriestrasse 23
 CH-6215 Beromünster LU
 Tel.: +41 (0)41 932 41 00
 Fax +41 (0)41 932 41 05
 E-mail info@indu-light.ch
 www.indu-light.ch

INDU LIGHT
 Tageslicht- und BrandschutzTechnik Vertriebs GmbH
 D'Orsay-Gasse 4/1
 A-1090 Vienna
 Tel.: +43 (0)1 319 25 00
 Fax: +43 (0)1 319 25 00 25
 E-mail contact@indu-light.at
 www.indu-light.at

